



SFC *easi-drive* C-RAD PNEUMATIC GUNS

TECHNICAL SPECIFICATIONS

MODEL No.	TORQUE RANGE (Nm)		SQUARE DRIVE Inches (mm)	FREE SPEED (rpm)	FREE SPEED (rpm)	WEIGHT (Kg)	OVERALL LENGTH A (mm)	GEARBOX DIA. B (mm)	OVERALL WIDTH C (mm)
	MIN	MAX		SINGLE	TWO SPEED (AUTO)				
C-RAD1	20	100	3/4"	290	---	2.5	186	62	70
C-RAD5	80	500	3/4"	65	---	2.7	198	62	70
C-RAD8	160	800	3/4"	40	---	3.0	200	62	70
C-RAD8A	350	800	3/4"	40	125	4.0	245	62	70
C-RAD10	190	1000	3/4"	30	---	4.3	229	72	80
C-RAD10A	450	1000	3/4"	30	170	5.3	286	72	80
C-RAD21	350	2100	1"	16	---	5.4	280	72	80
C-RAD21A	800	2100	1"	16	56	6.9	331	72	80
C-RAD27	550	2700	1"	11	---	5.7	266	76	80
C-RAD27A	850	2700	1"	11	53	7.3	316	76	80

* Other gun sizes are available – please ask for details.

- Air consumption: 848 L/min (30 ft³/min) @ 5.5 bar (80 psi)
- All units are supplied with easy switching from forward to reverse operation
- Sound Levels less than 85dB(A)
- Vibration – less than 2.5 m/s²

Smith Flow Control Ltd
Rev 0
20.01.04